

1 Identification

- Product identifier
- Trade name: Permanent Black Ink
- Relevant identified uses of the substance or mixture and uses advised against
Currently no such applications are identified
- Application of the substance / the mixture Permanent Marker Ink
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Viscot Medical, LLC.
32 West Street
East Hanover, NJ 07936
Phone: 973-887-9273
Fax: 973-887-3961
www.viscot.com
- Information department:
Tel.: 973-887-9273

- Emergency telephone number:
973-887-9273

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02



GHS05



GHS07

- Signal word Danger
- Hazard-determining components of labeling:
propan-1-ol
- Hazard statements
Highly flammable liquid and vapor.
Causes serious eye damage.
May cause drowsiness or dizziness.
- Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Use only outdoors or in a well-ventilated area.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/
shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
easy to do. Continue rinsing.

Trade name: Permanent Black Ink

(Contd. of page 1)

Immediately call a poison center/doctor.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

- HMSI-ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

| | | |
|------------|------------------------|---------|
| 71-23-8 | propan-1-ol | 25-50% |
| 64-17-5 | ethanol | 25-50% |
| 11099-03-9 | Cl. Solvent Black 5 | 2.5-10% |
| 872-50-4 | N-methyl-2-pyrrolidone | ≤1.0% |

- Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture
No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Wear protective clothing.
- Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

(Contd. on page 3)

Trade name: Permanent Black Ink

(Contd. of page 2)

- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility: Not required.
Further information about storage conditions:
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters

- Components with limit values that require monitoring at the workplace:

| 71-23-8 propan-1-ol (25-50%) | |
|------------------------------|---|
| PEL | 500 mg/m ³ , 200 ppm |
| REL | Short-term value: 625 mg/m ³ , 250 ppm Long-term value: 500 mg/m ³ , 200 ppm Skin |
| TLV | 246 mg/m ³ , 100 ppm |
| 64-17-5 ethanol (25-50%) | |
| PEL | 1900 mg/m ³ , 1000 ppm |
| REL | 1900 mg/m ³ , 1000 ppm |
| TLV | Short-term value: 1880 mg/m ³ , 1000 ppm |

- Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
- Breathing equipment:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)
USA

Trade name: Permanent Black Ink

(Contd. of page 3)

- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid
Color: According to product specification

- Odor: Product specific

- Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 78 °C (172 °F)

- Flash point: 13 °C (55 °F)

- Flammability (solid, gaseous): Not applicable.

- Ignition temperature: 360 °C (680 °F)

- Decomposition temperature: Not determined.

- Auto igniting: Product is not selfigniting.

- Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- Explosion limits:

Lower: 2.1 Vol %
Upper: 15.0 Vol %

- Vapor pressure at 20 °C (68 °F): 59 hPa (44 mm Hg)

- Density at 20 °C (68 °F): 0.86 g/cm³ (7.177 lbs/gal)

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not determined.

- Solubility in / Miscibility with

Water: Fully miscible.

- Partition coefficient (n-octanol/water): Not determined.

- Viscosity:

Dynamic at 20 °C (68 °F): 5 mPas
Kinematic: Not determined.

- Solvent content:

Organic solvents: 78.5 %

Solids content: 12.2 %

- Other information: No further relevant information available.

10 Stability and reactivity

- Reactivity

- Chemical stability

- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions: No dangerous reactions known.

- Conditions to avoid: No further relevant information available.

- Incompatible materials: No further relevant information available.

- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- Primary irritant effect:

- on the skin: No irritant effect.

(Contd. on page 5)

Trade name: Permanent Black Ink

(Contd. of page 4)

- on the eye: Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- Carcinogenic categories

| | | |
|---|---|----|
| · IARC (International Agency for Research on Cancer) | | |
| 62-53-3 | aniline | 3 |
| 101-61-1 | N, N, N', N' - tetramethyl - 4, 4' - methylenedianiline | 2B |
| 90-94-8 | 4, 4' - bis (dimethylamino) benzophenone | 2B |
| · NTP (National Toxicology Program) | | |
| 101-61-1 | N, N, N', N' - tetramethyl - 4, 4' - methylenedianiline | R |
| 90-94-8 | 4, 4' - bis (dimethylamino) benzophenone | R |
| · OSHA-Ca (Occupational Safety & Health Administration) | | |
| 62-53-3 | aniline | |


12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.



14 Transport information

| | |
|---|---------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · ADR | 1263 Paint |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |

(Contd. on page 6)
USA

Trade name: Permanent Black Ink

(Contd. of page 5)

| | |
|--|---|
| <ul style="list-style-type: none"> ADR  | |
| <ul style="list-style-type: none"> Class Label | 3 (F1) Flammable liquids 3 |
| <ul style="list-style-type: none"> IMDG, IATA  | |
| <ul style="list-style-type: none"> Class Label | 3 Flammable liquids 3 |
| <ul style="list-style-type: none"> Packing group DOT, ADR, IMDG, IATA | II |
| <ul style="list-style-type: none"> Environmental hazards: Marine pollutant: | No |
| <ul style="list-style-type: none"> Special precautions for user Danger code (Kemler): EMS Number: | Warning: Flammable liquids 33 F-E,S-E |
| <ul style="list-style-type: none"> Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> Transport/Additional information: DOT Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| <ul style="list-style-type: none"> ADR Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> UN "Model Regulation": | UN1263, Paint, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

| | |
|---|------------------------------------|
| <ul style="list-style-type: none"> Section 355 (extremely hazardous substances): | None of the ingredient is listed. |
| <ul style="list-style-type: none"> Section 313 (Specific toxic chemical listings): | None of the ingredients is listed. |
| <ul style="list-style-type: none"> TSCA (Toxic Substances Control Act): | All ingredients are listed. |
| <ul style="list-style-type: none"> Proposition 65 | |
| <ul style="list-style-type: none"> Chemicals known to cause cancer: | None of the ingredients is listed. |
| <ul style="list-style-type: none"> Chemicals known to cause reproductive toxicity for females: | None of the ingredients is listed. |
| <ul style="list-style-type: none"> Chemicals known to cause reproductive toxicity for males: | None of the ingredients is listed. |
| <ul style="list-style-type: none"> Chemicals known to cause developmental toxicity: | 64-17-5 ethanol |
| <ul style="list-style-type: none"> DSL/NDSL (Canada) | All ingredients are listed |
| <ul style="list-style-type: none"> Carcinogenity categories | |
| <ul style="list-style-type: none"> EPA (Environmental Protection Agency) | None of the ingredients is listed. |

(Contd. on page 7)

Trade name: Permanent Black Ink

(Contd. of page 6)

| | |
|--|----|
| · TLV (Threshold Limit Value established by ACGIH) | |
| 71-23-8 propan-1-ol | A4 |
| 64-17-5 ethanol | A3 |
| · MAK (German Maximum Workplace Concentration) | |
| 64-17-5 ethanol | 5 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| None of the ingredients is listed. | |

- GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- Signal word Danger
- Hazard-determining components of labeling:
propan-1-ol
- Hazard statements
Highly flammable liquid and vapor.
Causes serious eye damage.
May cause drowsiness or dizziness.
- Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Use only outdoors or in a well-ventilated area.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
In case of fire: Use for extinction: CO2, powder or water spray.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- National regulations:
- Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK | 50-100 |
- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 01/16/2015 / -
- Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International C of Dangerous Goods by Road) arriage
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMS: Hazardous Materials Identification System (USA)
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- * Data compared to the previous version altered.